

220 AUTHORIZED ACCESS POINT – FAMILY NAME

Field Definition and Scope

Preferred form of a family name.

It is formulated in accordance with the cataloguing rules or subject system in use by the agency which created it.

The subfield forming the base access point that identifies the family name is \$a. Qualifying data are recorded in \$c, \$d and \$f.

Field is repeatable for alternative script forms.

Subfields & Occurrence

Field/Subfield	Field/Subfield Name	Repeatability	Occurrence
220	AUTHORIZED ACCESS POINT – FAMILY NAME	R	O
a	Entry Element	NR	MA
c	Type of Family	NR	O
d	Places Associated with the Family	R	O
f	Dates	NR	O
j	Form Subdivision	R	O
x	Topical Subdivision	R	O
y	Geographical Subdivision	R	O
z	Chronological Subdivision	R	O
4	Relator Code	R	O
6	Interfield Linking Data	R	O
7	Script of Cataloguing and Script of the Base Access Point	NR	O
8	Language of Cataloguing and Language of the Base Access Point	NR	O

Indicators

Indicator	Value	Description
1	#	blank (not defined)
2	#	blank (not defined)

Subfields Description

\$a Entry Element

Family name in access point form.

This subfield must be present if the field is present. Not repeatable.

\$c Type of Family

Categorization or generic descriptor for the type of family that includes categorizations such as clan, dynasty, family unit, patriarchy, matriarchy, etc.

Not repeatable.

\$d Places Associated with the Family

Information pertaining to places where the family resides or resided or had some connection.

Repeatable.

\$f Dates

Dates of a family when they are required as part of the access point.

Not repeatable. (EX [3](#))

\$j Form Subdivision

Term added to a subject access point to further specify the kind(s) or genre(s) of material.

Agencies not using this subdivision should use \$x instead. Repeatable.

\$x Topical Subdivision

Term added to a subject access point to further specify the topic the subject access point represents.

Repeatable. (EX [2](#))

\$y Geographical Subdivision

Term added to a subject access point to specify a place in relation to a family which the subject access point represents.

Repeatable. (EX [2](#))

\$z Chronological Subdivision

Term added to a subject access point to specify the period in time in relation to a family which the subject access point represents.

Repeatable.

\$4 Relator Code

See specification of [Control Subfield 4](#).

Use when the field is embedded in fields 241, 242. The list of codes is to be found in UNIMARC/Bibliographic format, App. B. Repeatable.

\$6 Interfield Linking Data

See specification of [Control Subfield 6](#). Repeatable.

In cases of multiple identities occurring in the same record, i.e. when the 010 field is repeated, use to link the 010 field containing an ISNI with the 220 field containing the name to be associated with that ISNI.

\$7 Script of Cataloguing and Script of the Base Access Point

See specification of [Control Subfield 7](#). Not repeatable.

\$8 Language of Cataloguing and Language of the Base Access Point

See specification of [Control Subfield 8](#). Not repeatable.

Related Fields

420 VARIANT ACCESS POINT – FAMILY NAME
520 RELATED ACCESS POINT – FAMILY NAME
720 AUTHORIZED ACCESS POINT IN OTHER LANGUAGE AND/OR SCRIPT – FAMILY NAME

Examples

EX 1

220 ##\$aDuecker\$cFamily
EX 2
220 ##\$aBuchanan\$cClan\$xHistory\$yScotland
EX 3
220 ##\$aPahlavi\$cDynasty\$f1925-1979
EX 4
220 ##\$aРамескиды\$dдинастия\$f1206 – ок.1070 до н.э.
EX 5
220 ##\$aКуттер\$cсемья фотографов\$xВыставки\$yЛюксембург, г.\$z1999
EX 6
220 ##\$aBragança\$cCasa de

History

2009	New paragraphs: Notes on Field Contents, Subfields forming the base access point.
2009	New indicators and subfields/values: \$d Places associated with the family.
2009	New indicators and subfields/values: \$c Type of family.
2016	Update.