

520 RELATED ACCESS POINT – FAMILY NAME

Field Definition and Scope

Authorized form of the family name that is either related to the access point in the 2-- field.

It is formulated in accordance with the cataloguing rules or subject system in use by the agency which created it.

When a family name is part of “name/title or collective title”, the field 500 should hold a control subfield \$5 pos. 4.

Repeatable for each subsequent family name.

Subfields & Occurrence

Field/Subfield	Field/Subfield Name	Repeatability	Occurrence
520	RELATED ACCESS POINT – FAMILY NAME	R	O
a	Entry Element	NR	MA
c	Type of Family	NR	O
d	Places Associated with the Family	R	O
f	Dates	NR	O
o	International Standard Name Identifier (ISNI)	R	O
j	Form Subdivision	R	O
x	Topical Subdivision	R	O
y	Geographical Subdivision	R	O
z	Chronological Subdivision	R	O
0	Instruction Phrase	NR	O
2	Source	NR	O
3	Authority Record Identifier or Standard Number	NR	O
4	Relator Code	R	O
5	Relationship Control	NR	O
6	Interfield Linking Data	NR	O
7	Script of Cataloguing and Script of the Base Access Point	NR	O
8	Language of Cataloguing and Language of the Base Access Point	NR	O
R	Real World Object	O	R

Indicators

Indicator	Value	Description
1	#	blank (not defined)
2	#	blank (not defined)

Subfields Description

\$a Entry Element

Family name in access point form.

This subfield must be present if the field is present. Not repeatable.

\$c Type of Family

Categorization or generic descriptor for the type of family that includes categorizations such as clan, dynasty, family unit, patriarchy, matriarchy, etc.

Not repeatable.

\$d Places Associated with the Family

Information pertaining to places where the family resides or resided or had some connection.

Repeatable.

\$f Dates

Dates of a family when they are required as part of the access point.

Not repeatable.

\$o International Standard Name Identifier (ISNI)

The subfield \$o (International Standard Name Identifier) is used in field 510 to record the ISNI of the related identity. When the preferred access point of an authority record that contains field 010 is transferred to the 500/510/520 access point of another record (while establishing a link between both authority records), the number contained in the 010 field of the first record will also be transferred in a devoted subfield \$o. Repeatable.

Repeatable.

\$j Form Subdivision

Term added to a subject access point to further specify the kind(s) or genre(s) of material.

Agencies not using this subdivision should use \$x instead. Repeatable.

\$x Topical Subdivision

Term added to a subject access point to further specify the topic the subject access point represents.

Repeatable.

\$y Geographical Subdivision

Term added to a subject access point to specify a place in relation to a family which the subject access point represents.

Repeatable.

\$z Chronological Subdivision

Term added to a subject access point to specify the period in time in relation to a family which the subject access point represents.

Repeatable.

\$0 Instruction Phrase

See specification of [Control Subfield 0](#). Not repeatable.

\$2 Source

See specification of [Control Subfield 2](#). Not repeatable.

\$3 Authority Record Identifier or Standard Number

See specification of [Control Subfield 3](#). Not repeatable.

\$4 Relator Code

See specification of [Control Subfield 4](#). Repeatable.

\$5 Relationship Control

See specification of [Control Subfield 5](#). Not repeatable.

\$6 Interfield Linking Data

See specification of [Control Subfield 6](#). Not repeatable.

\$7 Script of Cataloguing and Script of the Base Access Point

See specification of [Control Subfield 7](#). Not repeatable.

\$8 Language of Cataloguing and Language of the Base Access Point

See specification of [Control Subfield 8](#). Not repeatable.

\$R Real World Object URI

See specification of [Control Subfield 3](#). Repeatable.

Notes on Field Contents

In fields 500, 510, 520, and 241 the code in the subfield \$4 used to designate the relationship between the person, corporate body, or family named in the field and the work or expression to which the record refers. In fields 500, 510, and 520, subfield \$4 should be used only when subfield \$5 character position 4 is set to value “a” (creator). Compare \$5/4 Relationship Code Between Agents and a Work or an Expression. The relator codes can be either numerical or alphabetical. The list of numerical codes is to be found in the UNIMARC/Bibliographic format, Appendix B. If greater precision in 500 is required for performers, the alphabetical codes that have been designed for field 146 (UNIMARC/Bibliographic format) can be used in subfield \$4. The list of codes values is found in the IAML web site <http://www.iaml.info/activities/cataloguing/unimarc/medium>. An agency requiring greater precision should use the numeric code followed by the more specific alphabetic code in a repeated subfield.

Related Fields

220 AUTHORIZED ACCESS POINT – FAMILY NAME

Examples

EX 1
220 ##\$aDuecker family
520 ##\$aDruecker family
EX 2
215 ##\$aЮгославия\$xИстория\$z20 в.
520 ##\$3RU\NLR\AUTH\661336492\$5g\$aКарагеоргиевич\$сдинастия
EX 3
200 #0\$aКонстантин Николаевич\$свеликий князь\$f1827 – 1892
520 ##\$3RU\NLR\AUTH\661238026\$5xxx1\$aРомановы\$ссемья

History

2009	New indicators and subfields/values: \$d Places associated with the family.
2009	New indicators and subfields/values: \$c Type of family.
2012	Additional subfields to field.
2012	Updated definition/scope: Field Definition, Occurrence.
2012	Updates.
2016	Updates.
2017	Text errata: Examples misprints.
2019	Editorial changes, added text from the restructured section Control Subfields, subfield \$4.
2023	Changed definition and scope.
2024	Text edit. New subfield \$R.