

## 035 OTHER SYSTEM IDENTIFIERS

### Field Definition and Scope

This field contains the identifier of records obtained from other sources.

### Subfields & Occurrence

Field/Subfield	Field/Subfield Name	Repeatability	Occurrence
035	OTHER SYSTEM IDENTIFIERS	R	O
a	System Identifier	NR	O
z	Cancelled or Invalid Identifier	R	O

### Indicators

Indicator	Value	Description
1	#	blank (not defined)
2	#	blank (not defined)

### Subfields Description

#### \$a System Identifier

A code for the organisation in parentheses followed by the system identifier for the record in that organisation's database. Since there are no internationally accepted codes, the codes from *MARC Code List for Organizations* are recommended. Otherwise, the full name of the agency or a national code may be used. Not repeatable.

#### \$z Cancelled or Invalid Identifier

Repeatable.

### Related Fields

001 RECORD IDENTIFIER	The identifier used as the unique identifier by the agency preparing the record.
-----------------------	--

### Examples

EX 1
001 b9301298
035 ##\$a(CiZaNSB)920701098
801 #0\$aHR\$bCiZaNSB\$c960507\$gPPIAK\$2unimyu
801 #2\$aGB\$bUk\$c960702
The original identifier of a record derived from one created by the National and University Library, Zagreb.
EX 2
035 #a(FrPBN)frBN001148436
801 #0\$aFR\$bFrPBN\$c951105\$gAFNOR\$2intermarc
801 #2\$aUS\$bDLC\$c970212
The identifier originally assigned by the Bibliothèque nationale in France.

### History

2000	New field.
2020	Errata / text edit. Field renamed.